Industrial Bitumen



Oxidised Bitumen for Waterproofing / Other Application

Material Safety Data Sheet

Identification of the substance/preparation and of the company/undertaking

Trade Name	Industrial Bitumen					
Intended Use	Waterproofing ,Industrial and Road Applications					
Company Name	STP Limited					
	43 Nehru Place					
	707 Chiranjiv Towers, New Delhi 110019, India					
	Phone: +91 11 4656 1359					
	Fax : +91 11 4656 1358					
Emergency Information	Phone: +91 81302 98888					
le le	Fax : +91 11 4656 1358					

[1] Composition / information on ingredients

Component	%	CAS No	
Bitumen	100 %	64742-93-4	

[2] Hazards Identification

Inhalation	Excessive inhalation can cause nausea, headache, intoxication.			
Ingestion	May cause irritation to the digestive tract and mouth causing			
goodao.ii	vomiting and abdominal pain			
Skin Contact	Prolonged contact will affect and dry the skin and may lead to			
	irritation and dermatitis.			
Eye Contact	Will cause intense smarting and irritation			

[3] First-aid Measures

Inhalation	Remove to fresh air. Give oxygen / artificial respiration if needed. Consult Doctor.
Ingestion	Do not induce vomiting. Give plenty of milk or water. Consult Doctor.
Eye Contact	Flush with clean water for minimum 15 minutes. Consult Doctor.
Skin Contact	Remove contaminated clothing. Apply proprietary skin cleaner, then wash with copious soap and water. Apply skin cream.

[4] Fire-fighting Measures

Extinguishing Media	Dry powder, CO2, Earth, Sand, Foam. Do not use Water.			
Special Fire Fighting procedures	Wear self contained breathing apparatus Full protective clothing. Spray drums with Water to keep cool.			
Unusual Fire & Explosion Hazards	Vapour is heavier than air. Combustion Produces toxic gases			

[5] Accidental Release Measures / Spills and Leaks

Steps to be taken in case material is	Absorb	onto	inert	material,	e.g.	sand,
	earth.	Put	into	suitable	cont	ainers.
released or spilled	Prevent	from (enterin	g water co	urses	

[6] Handling & Storage

Precautions for safe handling	Keep in tightly closed container in cool dry area from all sources of ignition				
Other precautions	Store away from oxidizing agents, peroxides, Food stuffs				

[7] Exposure Controls / Personal Protection

	Self contained breathing apparatus if in
Respiratory Protection (Type)	enclosed spaces. Otherwise, not normally
	required.

[8] Ventilation

Local Exhaust	Ensure adequate ventilation to comply with OEL.
Protective Gloves	Rubber, PVC
Eve Protection	Safety goggles Long sleeved overalls

[9] Physical & Chemical Properties

Appearance	Black solid
Odour	Asphalt odour
pH	N/A
Boiling Point/Boiling range ℃	N/A
Specific Gravity	1.0-1.05
Vapour pressure(MM mercury	N/A
Melting Point /Freezing point	Min 100'C
Water Solubility	Insoluble
Viscosity	N/A
Percentage Volatile by volume %	N/A
Evaporation Rate (Butyl Acetate=1)	N/A
Flash Point °C / Method used	>220°C
Lower Explosive limits	NA
Upper Explosive limits	NA

[10] Stability & Reactivity

Stability	Stable under normal conditions			
Conditions to avoid	High temperatures			
Incompatibility/Materials to avoid	Oxidising agents, strong acids, alkalis, Halogens			
Hazardous Decomposition Products	Combustion produces toxic gases			
Hazardous Polymerisation	Will not occur			

[11] Toxicological Information		
Non Toxic		

[12] Ecological Information		
Non pollutant		

[13] Disposal Consideration
Incinerate or landfill according to local regulations

[14] Transport Information

Class	N/A
Packaging Group	III
Classification Code	None
Hazard Ident. Number	9
UN Number	3257
RID-ADR	N/A
HI	N/A
Label	Class 9
Technical Name	Oxidized Bitumen

[15] Regulatory Information (Risk & Safety Phrases)

R10	N/A
R40/21	Harmful-Possible risk of irreversible
1140/21	effects. In contact with skin
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic
004	Environment
S24	Avoid contact with skin
S36/37/39	Wear suitable protective clothing, gloves
	and eye / face protection

[16] Other Health & Safety Information

Recommended uses and restrictions: See below

Source of key information used to compile SDS, CHIP regulations 1994. EH40

If this product is re-distributed and re-formulated for sale, details of its hazards and recommended methods for safe handling must be passed to customers. Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by a work activity using this product is undertaken before this product is used.

Note

The information contained in this Safety Data Sheet does not constitute the users own assessment of workplace risk as required by other Health & Safety Legislation (e.g. the Health and Safety at Work Act, 1974; the control of Substances Hazardous to Health Regulations, 1988). The data given here is based on current knowledge and experience. The purpose of this data sheet is to describe the products in terms of their safety requirements. The data does not signify any warranty with regard to the product's properties.