

# ShaliKote CT 103



STP Limited

Processed Coal Tar

## Description

**ShaliKote CT 103** is an excellent anti-corrosive solvent free type protective material, recommended where a better surface finish is desired. It has excellent adhesion, waterproofing and resistance against sea-water, oil and various chemicals. It is better than petroleum asphalt tar.

## Characteristics

Colour	Black	Specific gravity @ 30 °C	1.20 ± 0.02
Viscosity @ 30 °C, poise	105 ± 25	Drying Time, hrs, max	12
Toluene Insolubility, %, max.	12	Non Volatile Matter (1gm, 110 °C, 3 hr), %	85 ± 3

## Application

- Paint Industries, especially for ship or steel structure protection.
- Anti corrosive coatings.
- Refractory Industries.
- Graphite Industries.
- Aluminum Industries.
- Wood preservatives.

## Advantages

- Easy to apply.
- Excellent protection.
- Smooth finish for better appearance.

## Application Methodology

- Clean base metal thoroughly by sand blasting or otherwise. Before application, ensure that surface is dry and free from moisture, oil, grease, mill scale or rust.
- Stir **ShaliKote CT 103** thoroughly to achieve homogenous mix.
- Apply **ShaliKote CT 103** on dried and primed surface by brush or spray gun.
- Two coats of **ShaliKote CT 103** are recommended for concrete and three coats for metallic surfaces.

## Health & Safety

- **ShaliKote CT 103** is hazardous.
- Use goggles and hand gloves during application.
- Clean hands with warm soap water after application.

## Packing

Available in tanker and 200 L drum.

## Storage

Keep in cool and dry place, in air tight container, under the shed, away from heat.

---



**Advisory Cell**  
STP Limited  
**+91 81302 81114**  
Waterproofers to the Nation

**STP's Businesses**  
Waterproofing & Insulation  
Road Surfacing  
Pipeline Coating  
Repairs & Rehabilitation  
GARA (Grouts & Admixtures)  
Other Powder Products  
Sealant & Additives  
Epoxy Flooring  
Protective / Anti-Corrosive Coating  
Other Products



Visit us at : [www.stpltd.com](http://www.stpltd.com) or Email at : [info@stpltd.com](mailto:info@stpltd.com)