

ShaliPrime ERO



Two Component Anti Corrosion Red Oxide Epoxy Primer

STP Limited

Description

ShaliPrime ERO (formerly known as Red Oxide Primer) is a two component; cold cure epoxy based red oxide epoxy primer used as anti-corrosive primer. It is recommended for application on blast-cleaned metal surface.

Characteristics

Pot Life, hrs	3 – 4	Mix Specific Gravity	1.26 ± 0.02
Surface Dry, hrs	2 - 3	Theoretical Coverage, m ² / L / coat *	6 – 9
Dry Film Thickness	35 microns	Application Temperature	> 10 °C

* Depending upon surface condition.

Application

- As anti-corrosive primer on steel surfaces.

Advantages

- Excellent durability to all types of chemical environment.
- Excellent inter-coat bonding.

Application Methodology

- Oil and grease on the steel surface must be removed using suitable method, salts and other contaminants by (high pressure) fresh water cleaning prior to blasting.
- After blasting, clean the surface carefully from abrasives and dust.
- Abrasive blasting is the most effective method.
- Ensure surfaces are completely dry in depth and free of dirt, oil, grease or other contamination.
- On old steel surfaces having been exposed to salt water, excessive amounts of salt residues in pitting may call for wet abrasive blasting followed by dry abrasive blasting.
- **ShaliPrime ERO** may be over coated with conventional paints or two-pack epoxy paints/Polyurethane paints. Over-coating can be done after 6 – 8 hrs; however, it is recommended to coat after 12 - 24 hrs of application of primer to obtain superior performance.

Health & Safety

- The product should not come in contact with the skin and eyes, or be swallowed.
- Ensure adequate ventilation and avoid inhalation of vapours as some people are sensitive to resins, hardeners and solvents.
- Wear suitable protective clothing, gloves and eye protection.
- In case of contact with skin, rinse with plenty of clean water, then cleanse with soap and water. Do not use solvent to clean the contacted area.
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.
- If swallowed seek medical attention immediately - **do not** induce vomiting.

Packing

Available in 20 L container.

Storage

Store in a cool dry place, under shed, away from heat.

Shelf Life

12 months in original unopened sealed condition.



STP Limited
Advisory Cell
+91 81302 81114
Waterproofers to the Nation

STP's Businesses
Waterproofing & Insulation
Road Surfacing
Pipeline Coating
Repairs & Rehabilitation
GARA (Grouts & Admixtures)
Other Powder Products
Sealant & Additives
Epoxy Flooring
Protective / Anti-Corrosive Coating
Other Products

