

Description

ShaliSlip is shuttering oil / concrete form release agent that provides quick, easy and clean release of concrete from forms. It provides a smooth, flat surface, free of voids and defects. It will not transfer from forms and it leaves concrete surfaces unstained, ready for re-use almost instantly.

Characteristics

Physical Appearance	Yellowish brown low viscous liquid	Coverage	1 Ltr will cover approximately 20 to 36 m ² of forms depending upon application method and substrate.
Specific Gravity	0.83 ± 0.02		

Application

- Can be applied on metal, wood, plastic and fiberglass forms.
- Precast moulds & plywood.
- Equipment maintenance-scoots, buckets hoist and paving machines.

Advantages

- Acts as bond breaker and form cleaner.
- Eliminates voids, defects, build-up of concrete and mortar & provides fair finished exposed concrete.
- Non-staining will not wash off.
- Protects steel forms from rusting.
- Cuts clean-up time.
- Economical & easy to use.
- Protects plywood forms from bulging due to water absorption, thus increases the number of re-uses.
- Stripping of forms / de-shuttering becomes easy without hooking, thus increases shutter's life.

Application Methodology

- Remove dust, flakes, or other foreign particles by jet or dry air and clean the surface mechanically or with wire brush to ensure removal of loose rust particles.
- Stir the container well for removal of settlement, if any.
- Use ShaliSlip directly from container.
- Apply brush, roller or pump-up type sprayer. Coated forms may be used ½ hour after application of **ShaliSlip**.

Cleaning & Maintenance

Clean tools and equipments with solvent such as xylene, acetone or toluene.

Health & Safety

- Use mask, nose cover and hand gloves during application.
- Clean hands with soap water after application.
- Avoid contact with skin / eyes. In case of unlikely contact with eyes, rinse immediately with plenty of clean water, then cleanse with soap and lukewarm water and seek medical advice. Do not use solvent to clean the contacted area.

Packing

Available in 20 L and 200 L drum.

Storage

Store in a cool dry place under shed away from heat.

Shelf Life

12 months in original unopened sealed condition.



STP Limited
Advisory Cell
+91 81302 81114
Waterproofers to the Nation

STP's Businesses
Waterproofing & Insulation
Road Surfacing
Pipeline Coating
Repairs & Rehabilitation
GARA (Grouts & Admixtures)
Other Powder Products
Sealant & Additives
Epoxy Flooring
Protective / Anti-Corrosive Coating
Other Products

