

SuperKarGard BT

Anti-Corrosive Underbody Coating For Automobiles



Description

SuperKarGard BT is an asphalt based anticorrosive underbody coating for of all automobiles. **SuperKarGard BT** forms an effective barrier against corrosion by forming a continuous water resistant film. **SuperKarGard BT** provides a superior corrosion protection tough coating.

Characteristics

Colour	Black	Flash Point, °C	>23
Drying Time	30 minutes 24 hr	Solid content, %	Min 70
• Tack Free		DFT	100 microns
• Total drying		Theoretical Coverage, m ² /L	4 – 6
Specific Gravity @ 30 °C, g/cm ³	1.20 - 1.30		

Application

- Underbody coating for automobiles parts like chassis and mudguards.
- Vehicle undercarriages

Advantages

- Easy to apply.
- Excellent corrosion / abrasion / acid / alkali resistant, tough protective coating
- Fast Drying.
- No sagging on vertical surfaces.

Application Methodology

- Clean surface thoroughly and remove all foreign material, including oil and grease.
- Scale off all rusty particles with a wire-brush.
- Wash the surface and allow it to dry.
- Apply one coat of **SuperKarGard BT** with a brush / spray-gun on primed surface.
- Apply second coat after 4-5 hr of the first coat.

Health & Safety

- Lid of the containers should be firmly fixed, when not in use.
- **SuperKarGard BT** is inflammable and hence keep away from heat.
- Use goggles and hand gloves during application.
- Clean hands with warm soap water after application.

Packing

Available in 1 kg, 4 kg, 20 kg and 200 kg drums.

Storage

Keep in cool and dry place, under shed, away from heat.



Advisory Cell
STP Limited
+91 81302 81114
Waterproofers to the Nation

STP's Businesses
Waterproofing & Insulation
Road Surfacing
Pipeline Coating
Repairs & Rehabilitation
GARA (Grouts & Admixtures)
Other Powder Products
Sealant & Additives
Epoxy Flooring
Protective / Anti-Corrosive Coating
Other Products

