

ShaliKote CT

Coal Tar Based Solvent Free Protective Coating



STP Limited

Description

ShaliKote CT is an excellent coal tar based, anti-corrosive, solvent free protective coating material, recommended where a better surface finish is desired. It has excellent adhesion, waterproofing and resistance against sea-water, oil and various chemicals. It is better than petroleum asphalt tar.

Characteristics

Colour	Black	Consistency	Smooth and Uniform
Water Content, %, Max	0.5	Density at 20 °C, gm/cc	1.175 – 1.195
Toluene Insoluble, %	8-12	Viscosity at 20 °C	20 - 50 Poise
Distillation, °C <ul style="list-style-type: none">• 0-170• 170-270• 270-300 °C	0-1%	Flash Point, °C	>100
	15-20%	Ash, %, max	0.25
	10-15%	Phenol Content, %, max	1% max.

Application

- Anti-Corrosive coating for steel / concrete structures, specially for-
 - Ships / MS structure
 - Graphite / Aluminum / refractory industries.
 - Wood preservatives

Advantages

- Excellent protection
- Smooth finish for better appearance
- Easy to Apply

Application Methodology

- Remove dust, flakes, oil, grease or other loose foreign particles by sand blasting, iron brush or compressed air.
- Ensure that surface is dry and free from moisture.
- Stir **ShaliKote CT** thoroughly to achieve homogenous mix. For best result, use a variable speed drill mixer with a spiral type blade at the bottom of stirrer rod. The speed may be 400-600 rpm.
- Place the spiral blade at the bottom of the container before starting the mixer. This will help avoiding inducting air into the mass. Slowly move the stirrer head up to the surface while stirring. Do not remove the blade while still it is spinning. Continue the procedure for 5 minutes to have a homogeneous mix.
- Apply **ShaliKote CT** on dried and primed surface by brush or spray gun.
- For best results, apply two coats of **ShaliKote CT** by brush, roller or spray. Apply 2nd coat while the 1st coat is still tacky.

Health & Safety

- **ShaliKote CT** is hazardous.
- Avoid contact with skin / eyes and avoid swallowing.
- Ensure adequate ventilation and avoid inhalation of vapour.
- Wear suitable protective clothing, gloves and eye protection.
- In case of skin contact, rinse with plenty of clean water, then cleanse with soap and water. Do not use solvent to clean the contacted area.
- In case of eye contact, wash with plenty of clean water and seek medical advice.
- If swallowed, seek medical attention immediately. Do not induce vomiting.

Packing

Available in tanker and 200 L drum.

Storage

Keep in cool and dry place, in air tight container, under the shed, away from heat.



STP Limited
Enhancing Structures' Life

Product Range

- Waterproofing and Insulation
- Road Surfacing
- Sealants and Additives
- Pipeline Coating
- Protective / Anti-Corrosive Coating
- Epoxy Flooring
- Grouts / Admixtures
- RestoFix- Repair / Rehabilitation
- Other Construction Chemicals



Advisory Cell: +91 81302 81114