

ShaliKote[®] TC

Acrylic Based Gloss Clear Coat



Description

ShaliKote[®] TC is an emulsified acrylic resin-based primer. On drying it forms a clear transparent glossy & tough film with excellent water-repellency property.

Characteristics - Physical

State	Milky White Liquid	Dry Finish	Transparent
Solid, %	25 ± 1	Application temperature, °C	10 to 45
Density @ 25°C, gm / cc	1.03 ± 0.02	Drying Time, @ 30°C, RH 60%	Touch Dry 2 - 4 hrs.
Theoretical Coverage*, gm / m ² / coat	60 - 80		Hard Dry 12 - 24 hrs.

* Depending upon surface condition.

Application

- As top coat over **ShaliCryl[®] LM HI** and other water-based waterproofing membranes.

Advantages

- Good adhesion and flexibility.
- Water repellent.
- Moisture Insensitive.
- Chemical resistance.
- Provide good aesthetics.

Application Methodology

- **Surface Preparation**
 - Remove all loose gravel, dirt, oil, grease and foreign matter by jet of dry air before application.
- **Material Preparation**
 - Stir the material well before use.
- **Application of Material**
 - Apply **ShaliKote[®] TC** on existing membrane surface by brush / roller / spray.
 - A second coat may be applied for better properties.

Health & Safety

- Avoid contact with skin / eyes and avoid swallowing.
- Ensure adequate ventilation and avoid inhalation of vapor.
- Wear suitable protective clothing, gloves and eye protection
- In case of contact with skin, rinse with plenty of clean water, then cleanse with soap and water. Do not use solvent to clean the contacted area.
- In case of eye contact, wash immediately with plenty of clean water and seek medical advice.
- If swallowed seek medical attention immediately. Do not induce vomiting.

Packing

Available in 2, 5 & 20 kg bucket.

Storage

Store in a cool dry place, under shed, away from heat.

Shelf Life

12 months in original unopened sealed condition.



Product Range

- Waterproofing & Insulation
- Road Surfacing
- Sealants & Adhesives
- Pipeline Coatings
- Protective/Anti-Corrosion Coatings
- Epoxy and Flooring
- Grouts and Admixtures (GARA)
- RestoFix - Repair/Rehabilitation
- Other Construction Chemicals



Advisory Cell: +91 81302 81114 www.stpltd.com