

ShaliPrime[®] SM

Petroleum Resin Based Primer For Road Marking Paint for Concrete Surface



STP Limited

Description

ShaliPrime[®] SM is a petroleum resin based primer, designed for priming of concrete surface for application of thermoplastic road marking paints and other coating materials.

Characteristics

Viscosity, B4 Cup, 23 °C, min, sec.	20	Flash Point, Abel's Closed cup, min, °C	23
Specific Gravity at 23 °C, min	0.95	Drying Time. Max, minutes	15
Theoretical coverage*, m ² / L	10 -12	Volatile Matter, max, %	80

* Depending upon surface condition.

Application

- On concrete surfaces, bricks, natural stone and old bituminous road.
- Glazed tiles.
- Unglazed edges.

Advantages

- Easy to apply
- Facilitates bonding of ShaliMark on concrete surface.

Application Methodology

- Clean surface from oil, dirt, debris, paint and unsound concrete.
- Apply **ShaliPrime[®] SM** by brush, roller or spray.
- Apply second coat if surface is porous.
- Allow it to dry.
- If the primer gets hard dry, then recoating of the primer should be done in order to ensure good bonding with the ShaliMark.
- Apply ShaliMark on dried surface.

Health & Safety

- Use goggles and hand gloves during application.
- Clean hands with warm soap water after application.

Packing

Available in 20 L container.

Storage

Store in a cool dry, place under, shed away from heat.

Shelf Life

12 months in original unopened sealed condition.



STP Limited
Enhancing Structures' Life

Product Range

- Waterproofing and Insulation
- Sealants and Additives
- Protective / Anti-Corrosive Coating
- Grouts / Admixtures
- Other Construction Chemicals
- Road Surfacing
- Pipeline Coating
- Epoxy Flooring
- RestoFix- Repair / Rehabilitation



Advisory Cell: +91 81302 81114