

### Description

**TarFelt® BS** consists of a center core of hessian adequately coated on both sides with oxidized bituminous compound. Mica / sand is then spread over on both faces to prevent inter-sticking of layers.

### Characteristics

Breaking Strength, kg, Min	100 50	Heat Resistance at $68 \pm 2$ °C, 3 hr	No flow
<ul style="list-style-type: none"><li>Warp way</li><li>Weft way</li></ul>		Pressure Head Test at 300 mm height of water	No Leakage
		Storage sticking at $55 \pm 2$ °C, 18 hr	No Sticking
Pliability up to 15 °C	No Crack	Water absorption, %, Maximum	2
Weight, kg, Min	35	Bitumen content per Roll, Kg	18

### Application

**TarFelt® BS** is recommended as an economical waterproofing system. It can be applied over various types of surfaces such as concrete, corrugated asbestos or GI sheet, timber, shell / folded plates, etc. It is also used for waterproofing of silos, grain godowns, warehouses, wagons, trams, buses, etc.

### Advantages

- Proven first generation waterproofing membrane and recommended for non-critical over ground application.
- Economical with limited life.
- Dimensional stability with pliability to adopt to all contours.

### Application Methodology

- Specification regarding the nature of treatment should be decided depending on the type of structure and climatic conditions. For example, in severe climatic conditions, a heavy / extra heavy treatment should be adopted.
- Provide adequate number of drainage outlets of 100 mm diameter, at least for every 40 m<sup>2</sup> of roof area.
- Clean the surface thoroughly to make it free from any foreign material. Repair all undulation and surface defect like cracks, honeycombing etc.
- PCC / Cementitious coving of 75 mm radius shall be provided at all junctions between vertical and horizontal faces.
- Apply a coat of ShaliTex Primer minimum @ 0.25 L / m<sup>2</sup> and allow it to dry completely.
- Use STP Bitumen 85/25 as bonding material, which is to be prepared by heating it to the correct working temperature and spreading over the roof properly and uniformly @ 1.2 kg / m<sup>2</sup> per coat for waterproofing application or as specified.
- Unroll and fix **TarFelt® BS** by applying uniform pressure with hand for removal of any entrapped air.
- Provide overlap joints of 75 mm in longitudinal direction and 100 mm in transverse direction of the **TarFelt® BS** roll and seal it properly with hot bitumen.
- Terminate **TarFelt® BS** at the top of parapet if the height of parapet is up to 450 mm. In case the height of the parapet is above 450 mm, terminate **TarFelt® BS** at parapet in a groove 75 mm x 65 mm at a height of 150 – 300 mm from the finished roof level and groove shall be filled up with cement-sand mortar (1:4) with addition of ShaliPlast LW+ @ 200 ml / bag of cement.
- Top coat shall be finished with a layer of stone grit or pea gravel (6 mm and down size) which shall be laid by spreading over a hot bitumen coat @ 1.2 Kg / m<sup>2</sup> laid over the felt.

- In case of non-trafficable roof, over the finished coat of bitumen, apply a coat of SuperSilverShield, a bituminous based aluminium paint, @ 0.125 L / m<sup>2</sup>.
- For a trafficable roof, protect membrane with PCC / Tiles. In case of PCC, ShaliPolyFibre @ 600 gm/m<sup>3</sup> and ShaliPlast LW+ / STP No 1 (Liquid) @ 200 ml/bag of cement to be added to improve the resistance to crack formation and as well as waterproofing properties of screed.
- Use ShaliBond BS/CS cold adhesive wherever hot application is difficult or not permitted.
- For multi-layer treatment, stagger all the joints.

### Health & Safety

- Avoid contact with skin / eyes and avoid swallowing.
- Ensure adequate ventilation and avoid inhalation of vapour.
- Wear suitable protective clothing, gloves and eye protection.
- In case of skin contact, rinse with plenty of clean water, then cleanse with soap and water. Do not use solvent to clean the contacted area.
- In case of eye contact, wash with plenty of clean water and seek medical advice.
- If swallowed, seek medical attention immediately. Do not induce vomiting.

### Packing

Available in 1 m x 20 m roll.

### Storage

Keep in a cool dry place, under shed, away from heat. Do not stack more than three rolls in one column.



**STP Limited**  
Enhancing Structures' Life

#### Product Range

- Waterproofing and Insulation ■ Road Surfacing
- Sealants and Additives ■ Pipeline Coating
- Protective / Anti-Corrosive Coating ■ Epoxy Flooring
- Grouts / Admixtures ■ RestoFix- Repair / Rehabilitation
- Other Construction Chemicals



**Advisory Cell: +91 81302 81114**