

TarStilTar® Gr A / Gr B

Coal Tar Based Economical Anti-Corrosive Coating



Description

TarStilTar® Gr A / Gr B is Coal Tar based economical anti-corrosive coating.

TarStilTar® Gr A conforms to IS : 290/1961, Type A, and is recommended where a good quality quick drying product is desirable.

TarStilTar® Gr B conforms to IS : 290 / 1961 Type B.,

Characteristics

	TarStilTar Gr A	TarStilTar Gr B
Colour	Black	Black
Drying Time, hrs	4	24
Consistency	Brushable	Brushable
Dry film thickness per coat	50 Micron	60 Micron
Specific Gravity	1.13	1.15
Theoretical Coverage, m ² /L		
• On metal Surface	12	10
• On concrete Surface	10	8
• On wooden surface	10	8
Flash Point, °C	60	75

Application

- TarStilTar® Gr A is recommended for use on structural steel works, ship holds and other steel structures exposed to saline atmosphere and TarStilTar® Gr B is mainly used for corrosion protection of boats, barges and other structures exposed to saline atmosphere, where cost is a prime consideration and drying time of little consequence.
- It is in fact the most economical protecting medium for all kinds of steel and wood work.

Advantages

- Economical
- Easy to apply

Application Methodology

- The surface to be treated should be thoroughly cleaned and dried. All dirt scales and dust must be removed.
- Apply by brush to form a protective film on evaporation.
- Two coats are normally recommended. The period of protection is, however, considerably increased by the application of a third coat.
- Each subsequent coat should be applied when preceding coat has become dry and hard.
- Three coats of TarStilTar® Special™ are generally recommended.

Health & Safety

- Avoid contact with skin / eyes and avoid swallowing.
- Ensure adequate ventilation and avoid inhalation of vapour.
- Wear suitable protective clothing, gloves and eye protection.
- In case of skin contact, rinse with plenty of clean water, then cleanse with soap and water. Do not use solvent to clean the contacted area.
- In case of eye contact, wash with plenty of clean water and seek medical advice.
- If swallowed, seek medical attention immediately. Do not induce vomiting.

Packing

Available in 20 L and 200 L container.

Storage

Keep in cool and dry place, under shed away, from heat.



STP Limited
Enhancing Structures' Life

Product Range

- Waterproofing and Insulation ■ Road Surfacing
- Sealants and Additives ■ Pipeline Coating
- Protective / Anti-Corrosive Coating ■ Epoxy Flooring
- Grouts / Admixtures ■ RestoFix- Repair / Rehabilitation
- Other Construction Chemicals



Advisory Cell: +91 81302 81114