

PentaPhane Pale

Timber Preserver



Description

PentaPhane Pale is suitable to preserve timber structures used outdoors, like fence posts, posts, cabins etc. whether weathering is at peak.

Characteristics

Finish	No appreciable staining of wood	Flash Point, °C	35 minimum
--------	---------------------------------	-----------------	------------

Application

- In wooden doors, windows etc.
- Any object made of wood.

Advantages

- Can be applied by brush or spray.
- Cold immersion.

Application Methodology

- All sawing, cutting, framing and shaping should be done before immersing the timber.
- Apply **Pentaphane Pale** generously in 2 / 3 coats at minimum 12 hr intervals.
- First immersed timber in a tank of solution heated up to 65 °C for 1-2 hr. Then transfer to a tank of cold solution.
- This treatment can also be done in the reverse order.
- Impregnated timber with 5 L or more of **PentaPhane Pale** solution/cft.

Health & Safety

- Use goggles, gumboots, nose covers and hand gloves during application.
- Clean hands with warm soap water after application.
- It is inflammable.

Packing

Available in 1/2 L, 5 L and 20 L size. Bigger size also can be available for large requirement.

Storage

Keep in cool and dry place under shed away from heat.



Advisory Cell
STP Limited
+91 81302 81114
Waterproofers to the Nation

STP's Businesses
Waterproofing & Insulation
Road Surfacing
Pipeline Coating
Repairs & Rehabilitation
GARA (Grouts & Admixtures)
Other Powder Products
Sealant & Additives
Epoxy Flooring
Protective / Anti-Corrosive Coating
Other Products

