

ShaliFix[®] Putty M

2K Polyester Based Metal Putty



STP Limited

Description

ShaliFix[®] Putty M is a two component, high solid, polyester based putty to fill dents and pits of metal surface before painting.

Characteristics

Type	Two Parts Putty	Drying Time Minutes	
Colour	Off White / Grey	• Surface Dry	3
Pot Life @ 25 °C (100 gm), Minutes, Max	5	• Hard Dry	30
Mixing Ratio, Base : Catalyst	100 : 3	• Sanding	35
		Theoretical Coverage*	2-3
		m ² / Kg for 1.5mm	

* Depending upon surface condition.

Application

- Filler for pits and dents of automobiles / railway coach/ ship body / any other metal surface.

Advantage

- Excellent sand-ability.
- Fast Drying.
- Excellent adhesion to top coats.

Application Methodology

➤ Surface Preparation

- Ensure that the dents / pits portion of the metal surface is cleaned to obtain the base surface free from oil, grease and dust.
- Prime the surface with ShaliPrime Zn Ph / ShaliPrime Zn SL / ShaliPrime Zn R.

➤ Material Preparation

- Mix entire Component A (Base) into entire Component B (Catalyst) thoroughly by using spatula within one minute to achieve homogeneous mix.

➤ Application of Material

- Apply **ShaliFix[®] Putty M** on prepared surface with a knife / metal flat immediately.
- Allow the material to dry 35 minutes for sanding.

Health & Safety

- Avoid contact with skin / eyes and avoid swallowing.
- Ensure adequate ventilation and avoid inhalation of vapor.
- Wear suitable protective clothing, gloves and eye protection.
- In case of contact with skin, rinse with plenty of clean water, then cleanse with soap and water. Do not use solvent to clean the contacted area.
- In case of contact with eyes, wash immediately with plenty of clean water and seek medical advice.
- If swallowed seek medical attention immediately. Do not induce vomiting.

Packing

Available in 1 Kg pack.

Storage

Keep the packed material in a cool and dry place under shed

Shelf Life

6 months in original unopened sealed condition.



STP Limited
Enhancing Structures' Life

Product Range

- Waterproofing & Insulation ■ Road Surfacing
- Sealants & Adhesives ■ Pipeline Coatings
- Protective/Anti-Corrosion Coatings ■ Epoxy and Flooring
- Grouts and Admixtures (GARA)
- RestoFix - Repair/Rehabilitation ■ Other Construction Chemicals



Advisory Cell: +91 81302 81114