

# ShaliPrime<sup>®</sup> PUM

Aromatic Polyurethane Primer



STP Limited

## Description

**ShaliPrime<sup>®</sup> PUM** (formerly known as ShaliPrime Penetration) is single component polyurethane resin based low viscous highly penetrative primer.

## Characteristics

Working Life @ 30 °C, hrs	6 - 7	Surface Dry, @ 30 °C, minutes	35 – 45
Recoating Time, hrs	2	Theoretical Coverage*, m <sup>2</sup> / L / coat	4 - 5
DFT in microns	40 - 50		
Density @ 30°C, gm/cc	0.92-0.97		

\* Depending upon surface condition.

## Application

- Concrete / metal surfaces.

## Advantages

- Better adhesion and flexibility.
- Chemical resistance.
- Improved performance over manually prepared concrete surfaces.

## Application Methodology

### ➤ Surface Preparation

- Prepare the surface by mechanical grinding or other suitable method.
- Remove dust, flakes, oil, grease or other loose foreign particles by sand blasting, iron brush or compressed air. Remove old painting using surface grinder.
- Remove old painting using surface grinder.
- For best bond, concrete surface must be slightly textured.
- Allow it to dry before priming.
- Ensure that concrete must be cured at least 28 days and moisture content is below 5%.
- For metallic substrate there should be no moisture content prior to application of the primer.

### ➤ Application of Material

- Apply **ShaliPrime<sup>®</sup> PUM** by brush / airless spray on cleaned surface.
- Once opened, drum should be used completely.

## Health & Safety

- Avoid contact with skin / eyes and avoid swallowing.
- Ensure adequate ventilation and avoid inhalation of vapour.
- Wear suitable protective clothing, gloves and eye protection.
- In case of skin contact, rinse with plenty of clean water, then cleanse with soap and water. Do not use solvent to clean the contacted area.
- In case of eye contact, wash with plenty of clean water and seek medical advice.
- If swallowed, seek medical attention immediately. Do not induce vomiting.

## Packing

Available in 1 L and 20 L container.

## Storage

Store in a cool dry place, under shed, away from heat and sunlight.

## Shelf Life

6 months in original unopened sealed condition.



  
**STP Limited**  
*Enhancing Structures' Life*

**Product Range**

- Waterproofing & Insulation
- Sealants & Adhesives
- Protective/Anti-Corrosion Coatings
- Grouts and Admixtures (GARA)
- RestoFix - Repair/Rehabilitation
- Road Surfacing
- Pipeline Coatings
- Epoxy and Flooring
- Other Construction Chemicals

  
85  
Years of  
Trust

**Advisory Cell: +91 81302 81114**

[www.stpltd.com](http://www.stpltd.com)