

# ShaliPrime<sup>®</sup> PW CT

Synthetic Primer for Coal Tar Tape



STP Limited

## Description

**ShaliPrime<sup>®</sup> PW CT** is resin based synthetic primer containing unmodified chlorinated rubber and special grade of coal tar pitch. It is applied without heating and produces an effective bond between the surface to be protected and Coal Tar Tape wrapped thereon.

It conforms to AWWA C 203 : 2015, IS 10221 and IS 15337 : 2003 and EIL Specification.

## Characteristics

Specific Gravity at 30 °C	1.00 – 1.10	Volatile Matter, 100-110 °C, Loss of mass, %	75 Max
Flash Point (Abel), °C, Min	23	Drying Time, Minutes, Tack free	5 - 15
Viscosity (Flow Time), 20 °C, No. 4 Flow cup, sec.	35 - 60	Theoretical Coverage *, m <sup>2</sup> / L	8 - 10
Filler Material	Nil	Applicable	By Brush / Spray
DFT, micron	30 ± 5		

\* Depending upon surface condition.

## Application

**ShaliPrime<sup>®</sup> PW CT** is applied as a primer over steel pipelines for providing bond between PipeWrap CT and primed steel pipes.

## Advantages

- Excellent bonding of Coal Tar Tape and pipeline surface with improved electrical insulation properties
- Easy to Apply
- Economical and cost effective.

## Application Methodology

### ➤ Surface Preparation

- Clean the surface free of all foreign matter, dust, oil or grease, specially of chloride contamination.
- Ensure not to apply when temperature is less than 5.
- Blast clean surface of the pipe by shot and grit to a greyish matt appearance to SA 2 ½.

### ➤ Application of Material

- Apply **ShaliPrime PW<sup>®</sup> CT** at the rate of 0.30 L / m<sup>2</sup> on completely dry surface.

## Health & Safety

- Avoid contact with skin / eyes and avoid swallowing.
- Ensure adequate ventilation and avoid inhalation of vapour.
- Wear suitable protective clothing, gloves and eye protection.
- In case of skin contact, rinse with plenty of clean water, then cleanse with soap and water. Do not use solvent to clean the contacted area.
- In case of eye contact, wash with plenty of clean water and seek medical advice.
- If swallowed, seek medical attention immediately. Do not induce vomiting.

**Packing**

Available in 20 L and 200 L steel drum.

**Storage**

Keep in cool and dry place, under shed, away from heat.

**Shelf Life**

12 months in unopened sealed condition.





**STP Limited**  
*Enhancing Structures' Life*

### Product Range

- Waterproofing and Insulation
- Road Surfacing
- Sealants and Additives
- Pipeline Coating
- Protective / Anti-Corrosive Coating
- Epoxy Flooring
- Grouts / Admixtures
- RestoFix- Repair / Rehabilitation
- Other Construction Chemicals



**Advisory Cell: +91 81302 81114**

