

# TankMastic® 100

100 Micron Single Coat Bituminous Anti-Corrosive Coating



## Description

**TankMastic® 100** is a specially formulated anti-corrosive bituminous coating for railway tracks and other metallic / concrete structure. **TankMastic® 100** gives 100 micron DFT in single coat by single feed spray gun application and is tasteless, odourless and non-toxic. **TankMastic® 100** cure to a hard film, having excellent resistance to water, mild acid, alkali and major common chemical.

It conforms to IS: 9862/1981 as well IS: 158/1981.

## Characteristics

Colour	Black	Specific Gravity	1.00 ± 0.02
Drying Time, hr		Theoretical Coverage, m <sup>2</sup> /L*	
• Touch dry	2 – 4	• On Metal Surface	4 - 5
• Hard dry	6 - 8	• On Concrete Surface	3.5 – 4.5
Consistency	Uniform; applicable by brush or spray gun	DFT, Microns*	125 ± 25
		Flash Point, °C	35

\* Depending upon surface condition and ambient temperature around 40 °C.

## Application

- Railway tracks and other metallic / concrete structures.
- Underbody of railway coach wagons and other vehicles.

## Advantages

- Easy to apply by brush / single feed spray gun.
- Dries fast to form a tough abrasion resistant coating.
- Provides an excellent anti-corrosive / protective coating for wide range of applications
- Resistant to diluted acids and alkalis with excellent water resistance property.

## Application Methodology

- **Surface Preparation**
  - Remove all loose gravel, dirt, oil, grease and foreign matter by jet of dry air and clean the surface mechanically or by grinding to make it smooth before application.
- **Material Preparation**
  - Stir **TankMastic® 100** by a slow speed mixture (approx. 400 rpm) fitted with a suitable mixing paddle to ensure a homogenous mix.
  - After stirring, wait for the product to settle in order to let entrapped air escape.
- **Application of Material**
  - Apply **TankMastic® 100** by brush / spray gun on prepared surface.

## Health & Safety

- Avoid contact with skin / eyes, and avoid swallowing.
- Ensure adequate ventilation and avoid inhalation of vapour.
- Wear suitable protective clothing, gloves and eye protection.
- In case of skin contact, rinse with plenty of clean water, then cleanse with soap and water. Do not use solvent to clean the contacted area.

- In case of eye contact, wash with plenty of clean water and seek medical advice.
- If swallowed, seek medical attention immediately. Do not induce vomiting.

### **Packing**

Available in 20 L and 200 L drum.

### **Storage**

Keep in cool and dry place in air tight container under shed away from heat.

### **Shelf Life**

12 months in original unopened sealed condition.

---



**Advisory Cell**  
STP Limited  
**+91 81302 81114**  
Waterproofers to the Nation

**STP's Businesses**  
Waterproofing & Insulation  
Road Surfacing  
Pipeline Coating  
Protective / Anti-Corrosive Coating  
GARA (Grouts & Admixtures)  
Sealant & Additives  
Repairs & Rehabilitation  
Epoxy Flooring



